



OUTBOARD ENGINE OIL **2T**

Product Description:

OUTBOARD ENGINE OIL 2T is a high performance ashless 2-stroke engine oil for use in modern cooled outboard engines where NMMA TC-W3 is required

OUTBOARD ENGINE OIL 2T is based on high performance mineral base oil in combination with a specially selected additive technology to ensure the following properties.

- Excellent lubricity.
- Protection against wear and rust.
- High protection against scuffing and deposit forming.
- Easy mixing and stable mixture even at low temperatures

OUTBOARD ENGINE OIL 2T meets the following performance criteria:

NMMA TC-W3®

Property	Unit	Test Method	Typical Value
Density@15°C	kg/m ³	ASTM D4052	874
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	43.2
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	6.8
Viscosity Index		ASTM D2270	116
Flash Point COC	°C	ASTM D92	>90
Pour Point	°C	ASTM D7346	-33
Total Base Number	mgKOH/g	ASTM D2896	8.7
Sulphated Ash	%Wt	ASTM D78	0.15

Product Nr: 42960

Date Superseded: 08-02-2018

Date Issued: 13-12-2019

Revision nr: 03

